


REVISION RECORD

REV	ECN#	DESCRIPTION	BY	DATE
A0			Shaey	2022-03-26

Table 1

Length	Tolerances
≤15m	+150 mm/-0 mm
>15m	+1%L mm/-0 mm

3.0mm 12F SM mini Cable



SECTION A-A / B-B

Type A

Side A Fiber Hole Position	Cable Fiber Color	Side B Fiber Hole Position
1	BLU	1
2	ORN	2
3	GRN	3
4	BRN	4
5	STL	5
6	WHT	6
7	RED	7
8	BLK	8
9	YEL	9
10	VIO	10
11	PNK	11
12	AQU	12

Type B

Side A Fiber Hole Position	Cable Fiber Color	Side B Fiber Hole Position
1	BLU	12
2	ORN	11
3	GRN	10
4	BRN	9
5	STL	8
6	WHT	7
7	RED	6
8	BLK	5
9	YEL	4
10	VIO	3
11	PNK	2
12	AQU	1

Table 2

TYPE	MPO/PC/SM/12F(STD) 1310/1550nm
IL	≤0.60 dB
RL	>45 dB

TOLERANCE ON DECIMALS		
	±MM	±°
X		
X.X	±0.1	±0.1°
X.XX	±0.05	±0.05°
X.XXX	±0.005	±0.005°

PART NAME MPO PC(F)-MPO PC(F)-3.0mm-12F-SM-xxxM (Type A&B)		DRAWING NO.		REV A0
SCALE	QTY	PAGE	THIRD ANGLE PROJECTION	
UNIT mm	MATERIAL		APPROVED	
DRAW	CHKD			