


REVISION RECORD

REV	ECN#	DESCRIPTION	BY	DATE
A0			Shaey	2022-03-26

Table 1

Length	Tolerances
≤15m	+150 mm/-0 mm
>15m	+1%L mm/-0 mm

L+T
 3.0mm 12F OM3 mini Cable



Type A		
Side A	Cable	Side B
Fiber Hole Position	Fiber Color	Fiber Hole Position
1	BLU	1
2	ORN	2
3	GRN	3
4	BRN	4
5	STL	5
6	WHT	6
7	RED	7
8	BLK	8
9	YEL	9
10	VIO	10
11	PNK	11
12	AQU	12

Type B		
Side A	Cable	Side B
Fiber Hole Position	Fiber Color	Fiber Hole Position
1	BLU	12
2	ORN	11
3	GRN	10
4	BRN	9
5	STL	8
6	WHT	7
7	RED	6
8	BLK	5
9	YEL	4
10	VIO	3
11	PNK	2
12	AQU	1

Table 2	
TYPE	MPO/PC/MM/12F(STD)
	850nm
IL	≤0.60 dB
RL	>25 dB

TOLERANCE ON DECIMALS			PART NAME		DRAWING NO.		REV
X	±MM	±°	MPO PC(M)-MPO PC(M)-3.0mm-12F-OM3-xxxM (Type A&B)		PAGE		A0
X.X	±0.1	±0.1°	SCALE	QTY	THIRD ANGLE PROJECTION		
X.XX	±0.05	±0.05°	UNIT	MATERIAL	APPROVED		
X.XXX	±0.005	±0.005°	mm	CHKD	APPROVED		
DRAW			CHKD		APPROVED		